

ELECTRIC SCISSOR LIFTS

0608 (2132) / 0808 (2732)

Compliant with CE/EAC standards

PRODUCT HIGHLIGHTS

Efficient and Environmentally Friendly

- Small turning radius, flexible operation in narrow spaces
- Standard forklift slot for efficient equipment transportation
- Folding guardrails for easy transport

Reduced Maintenance Costs

- Double-door design for easy maintenance
- Troubleshooting for quick fault diagnosis
- High quality parts and components

More Reliable Performance

- Battery voltage early warning to ensure battery life
- Bumper rail protection
- The pothole protection reporting and horizontal protection system guarantee safety of operation



Standard Features

| | | |
|-------------------------|-------------------------------------|---------------------------|
| 2WD×2WS | Maintenance-free battery | Fault diagnosis system |
| Non-marking tires | Proportional control | Emergency lowering system |
| Emergency stop | Electrophoretic painting | Tilt protection system |
| Flashing beacon | Forklift pockets and lifting points | Overload sensing system |
| Foldable guardrail | Automatic pothole protection | Manual storage box |
| Drivable at full height | Bumper rails | Auto braking system |
| Horn & buzzer | | |

Options & Accessories

| | | |
|------------|--------------------------------|----------------------------|
| RCBO | AC power to platform | Platform work light |
| Footswitch | Overhead anti-collision device | Telematics-ready connector |

SINOBOOM™

PARTNERS IN ACCESS™

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ELECTRIC SCISSOR LIFTS 0608 (2132) / 0808 (2732)

Compliant with CE/EAC standards

| Model | 0608 (2132) | 0808 (2732) |
|--|---|---|
| Dimensions | | |
| Max Working Height (Indoor/Outdoor) | 8.3 m (27'3") | 10.1 m (33'2") |
| A Max Platform Height (Indoor/Outdoor) | 6.3 m (20'8") | 8.1 m (26'7") |
| B Platform Extension | 0.9 m (3') | 0.9 m (3') |
| C Length-Stowed | 2.39 m (7'10.1") | 2.39 m (7'10.1") |
| D Width-Stowed | 0.81 m (2'8") | 0.81 m (2'8") |
| E Height-Stowed (Rails Folded) | 1.83 m (6') | 1.96 m (6'5") |
| E Height-Stowed (Rail Unfolded) | 2.22 m (7'3.4") | 2.35 m (7'8.5") |
| F Wheelbase | 1.85 m (6'0.8") | 1.85 m (6'0.8") |
| Ground Clearance (Pothole Guard Stowed) | 0.073 m (3") | 0.073 m (3") |
| Ground Clearance (Pothole Guard Deployed) | 0.024 m (0.95") | 0.024 m (0.95") |
| Platform Dimensions (L×W×H) | 2.25 m×0.81 m×1.1 m (7'4.6"×2'7.9"×3'7") | 2.25 m×0.81 m×1.1 m (7'4.6"×2'7.9"×3'7") |
| Performance | | |
| Platform Capacity | 380 kg (838 lbs) | 250 kg (551 lbs) |
| Extension Platform Capacity | 120 kg (265 lbs) | 120 kg (265 lbs) |
| Platform Allowable Occupants (Indoor/Outdoor) | 2 persons/1 person | 2 Persons(Indoor Only) |
| Drive Speed (Stowed) | 0~3.2 km/h (0~2 mph) | 0~3.2 km/h (0~2 mph) |
| Drive-Speed (Raised) | 0~0.8 km/h (0~0.5 mph) | 0~0.8 km/h (0~0.5 mph) |
| Lift Time (Unloaded) | 25 s~30 s | 30 s~35 s |
| Lower Time (Unloaded) | 30 s~35 s | 34 s~39 s |
| Gradeability | 25% | 25% |
| Max Allowable Inclination (Front-To-Back/Side-To-Side) | 3°/1.5° | 3°/1.5° |
| Turning Radius (Inside/Outside) | 0 m/2.1 m (0/6'10.7") | 0 m/2.1 m (0/6'10.7") |
| Tire Size/Type | 380×125 mm (15×5")/solid | 380×125 mm (15×5")/solid |
| Power | | |
| Drive×Steer | 2 WD×2 WS | 2 WD×2 WS |
| Power Source (V/kW) | 24 V DC /3.3 kW | 24V DC /3.3 kW |
| Hydraulic Tank Capacity | 14L (3.1gal (UK) /3.7gal(US)) | 14L (3.1gal (UK) /3.7gal(US)) |
| Batteries | 24 V,220Ah (Lead Acid Battery) | 24 V,220Ah (Lead Acid Battery) |
| Charger (Input/Output) | 100~240 V AC/30A | 100~240 V AC/30 A |
| Weight | | |
| Weight (Indoor/Outdoor) | 1,770 kg (3,903 lbs) | 1,970 kg (4,344 lbs)(Indoor Only) |
| Standards Compliance | CE/EAC | |

